



Process of Waste2GridS project:

Triple-mode grid-balancing plant based on biomass gasification and solid-oxide cell stacks

Ligang Wang, Jan Van herle (EFPL)




e-EUBCE 2020 *Bioeconomy's role in the post-pandemic economic recovery*

28th European Biomass Conference & Exhibition

VIRTUAL | 6 - 9 July

Biomass/waste-to-energy

- The role of biomass in the future with high vRES share




Single-purpose biomass-fed plant will suffer from

- **high OPEX due to biomass collection**
- **low annual operating hours**

A biomass power plant with power-to-fuel capability?

Triple-mode grid balancing plant




- Reversible operation
- High reactant flexibility

Grid-scale application: Gasification → Syngas → rSOC → End product

Waste2GridS concept

Three-mode grid-balancing plant with power-to-methane



- **Additional profit by grid-balancing services**
- Enhanced annual operating hours
- Reduced CAPEX by sharing the stacks & others
- **Enhanced balancing capability and capacity**
- **Unlimited energy storage capacity**
- **No CO₂ capture needed for waste-to-biofuel**

Waste2GridS project (2019—2020)



- **Economic feasibility** study of the plant deployment at **2030**

Technical potential

Business cases

Bottlenecks

WP1
Zone identification


Grid balancing needs
Waste availability

WP2
System design

Optimal plant design
Regional integration

WP3
Techno-economics

Upscaling strategy
Techno-economics



Overall implementation and timeline


2019.01

Technical potential


M18 **Business cases** 2020.12

RES-dominated power generation zones

(solid lines: electricity transmission or distribution lines) (grey: MSW; blue: commercial; light blue: agri&forest)




Waste availability



Case studies

(grey dashed curves: waste supply)




W2G plant for zone A
(MW level, with design 1)

W2G plant for zone B
(tens of MW level, with design 5)

W2G plant for zone C
(100 MW to 1 GW level, with design n)

Optimal plant design
with technology superstructure
(various technologies considered)




**Optimal design selection,
plant sizing & scheduling**

Progress – Grid flexibility needs


- vRES-dominated zones for **2030**



Annual vRE contribution to electricity consum.



Annual UP/DOWN electricity (TW h)




- VERY** high vRE share (>100%) to have big DOWN need: DK1 and Bornholm
- Several to several tens of TW h (**2-8 GW**) for large market: DK1, DK2, SUD
- Tens to hundreds of GW h (**40-100 MW**) for Bornholm

Progress – Technical waste potential


- Local waste availability predicted for **2030**



Local **exploitable** waste excluding **competing use**



Energy comparison




- MSW & Agri amount comparable**

- Balancing energy & waste potential at the same magnitude**

Progress – Optimal plant concept design

- Design pool

- EFG-TOR-HC-SE-STN ○ EFG-TOR-CC-CE-STN ○ FICFB-TRF-CC-SE-STN ○ PG-HC-SE-STN
- EFG-TOR-CC-SE-STN ○ FICFB-HTS-RADP-HC-SE-STN ○ FICFB-TRF-CC-CE-STN





- A variety of plant designs with a wide range of efficiency
- Eff. of **PowGen (36-70%)**, **PowSto (40-76%)** and **PowNeu (32-62%)**, much higher than exiting Biomass-to-Power or -Fuel plants


Progress – Grid integration

- Modified Dispa-SET platform for multiple scenarios


The scenario taking all flexibility needs



3 plants




12 plants



- Critical information provided for economic evaluation
 - Plant number & sizes
 - Plant scheduling and auxiliary requirement
- PowNeu mode might have large operation share!**

Progress – Biomass supply chain



- Create supply chain for the plants expected



Progress – Upscale strategy



How to scale up from kW-level stack to MW-level plant?



- Potential way of biomass utilization for grid balancing
 - **Efficiency, flexibility, possibly economic, new service**
- An optimization methodology for optimal plant deployment
- Large grid flexibility needs exist for DK1, Bornholm (>100% vRES / electricity consumption); **hardly be coped with a specific technology.**
- Local waste supply within the **same order of magnitude** as flexibility needs
- Upscaling strategy of SOC to MW level developed

- Grid integration & supply chain design ready
- Specific **business cases in DK and IT** will be delivered in next half year



Acknowledgement:

This project has received funding from the Fuel Cells and Hydrogen Joint Undertaking under grant agreement No 826161.

This Joint Undertaking receives support from the European Union's Horizon 2020 research and innovation programme, Hydrogen Europe and Hydrogen Europe research.

